

# StellaOffice-LGW

Model number: SD-RP1002-LGW-4P  
 Frequency: 800 / 900 / 2100



## Frequency Specifications:

Frequency bands(Mhz):	(791 - 862MHz) + (880 - 960MHz) + (1.92 - 2.17GHz)
Coverage:	(1000m <sup>2</sup> per antenna X 4) = ~15 rooms
Number of People:	Unlimited
Gain:	Uplink Gp > 50dB      Downlink Gp> 60dB
Pass band ripple:	< 4dB
I/O impedance:	50 ohm/SMA female connector
Max uplink/downlink signal strength:	20dBm / 10dBm
Ambient Temperature:	-30°C to +70°C
Power supply input:	110 - 240V AC
Power supply output:	12v DC
Oscillation Control	Automatic
Level Control:	Automatic*
Uplink Switch Off	Yes**
AGC Range	30db
Surge protection	SMA connectors DC grounded, 12V DC port MOV protected

## Antenna Specifications:

### Indoor antenna

### outdoor antenna

Nominal Gain	6.4dBi / 9.4dBi	10dBi
3dB beam Pattern	60° x 60°	60° x 50°
Bandwidth	790-960MHz + 1710-2700MHz	790-960MHz + 1710-2700MHz
VSWR	<1.4	<1.5
Front to Back Ratio	> 20dB	> 20dB
Polarization	Vertical	Vertical
Power Rating	50W	50W
Impedance	50-OHM	50-OHM
Termination	SMA male	N-Female
Cross Pol. Discrimination	-20dB	-20dB
Dimensions	210 x 180 x 43mm	442 x 205 x 62mm
Weight	0.68kg	1.2kg
Wind velocity	126km/hr	140km/hr
Working temperature	-40°C to +65°C	-40°C to +65°C

## Power Supply Specification:

AC	100-240V	50-60Hz
DC input	12V	2.2A
Typical power usage		26W

## Mechanical Specification:

Length	40cm
Width	19cm
Depth	3.5cm
Weight	1.2kg
Mounting	6 x 5mm holes for mounting

\* Automatically adjusts during installation. Thereafter, automatically adjusts for seasonal variation in pathloss between Basestation and Outdoor Antenna.

\*\* The uplink amplifiers switch off when the repeater is not in use, thus reducing the uplink noise to almost zero. When the repeater is in use (eg phone call being made), the uplink amplifier switches on for the duration of the call and a blue LED switches on indicating this is the case.

Note: Specifications subject to change without notice.